



STRUCTURE

The frame is made of solid beech with glued mortise and tenon joints. The seat is fitted with Nosag springs.

BACK: 10 mm thick, press-formed multiplex panel with elastic webbing.

PADDING

SEAT - 5 successive layers: 10 mm 55 kg/m3 polyether foam, 40 mm 55 kg/m3 HR foam, 20 mm 45 kg/m3 HR foam, 20 mm 43 kg/m3 HR foam and a layer of 250 g/m3 wadding.

BACK - 4 successive layers: 10 mm polyether foam 55 kg/m3, 10 mm HR foam 35 kg/m3, 20 mm HR foam 55 kg/m3 and 20 mm HR foam 35 kg/m3

FEET

Solid beech, oak or walnut, available in various shades.

GLIDERS

plastic (for tiles, natural stone, hard floors)

felt (for parquet)

metal (for carpets)

optional, at extra cost, PTFE/Teflon (for intensive use)

DIMENSIONS (CM)



LENA RO6

(LENA DUO UNI H40 PB +A)

VERSIONS

LENA R0625 (fixed)

DISTRIBUTION

collection RETAIL X'clusive

collection CONTRACT générale

DESIGN

Pierre Wegnez

LABEL

MOBITEC Label

SPECIAL FEATURES

UPHOLSTERY

Cover	Fixed (cm)*	Loose fixed (cm)*	Loose cover (cm)*	Leather (m²)*
Uni	315	-	-	-
Bi**	(a) -	(a) -	(a) -	(a) -
	(b) -	(b) -	(b) -	(b) -

* fabric or faux leather metres needs in cm on a roll width of 140cm, leather needs per m².

Leather and faux-leather upholsteries (always fixed)

** The first upholstery (a) is always used for the seat.

SECURITY

This product does not require any specific safety warnings, as it is safe to use under normal conditions.

WEIGHT & PACKAGING

Product net weight: 22.6 Kgs Number of pieces per carton: 1 pc(s) Carton gross weight: -Carton dimensions: 154x82x76