

LOTUS CO1

(LOTUS H47 PB -A)

Mobitec Label

VERSIONS LOTUS CO1 (fixed) DISTRIBUTION Retail/Contract Collection DESIGN Jana Sarlette LABEL

STRUCTURE

Under press formed 10mm plywood shell

PADDING

Seat: Padded with 4 successive layers: 20mm layer Super E foam, 20mm layer of 43kg/m3 HR foam, 20mm layer of 45kg/m3 HT foam, 5mm T25 foam.

Backrest: Upholstered with 2 successive layers: 20mm layer of 43kg/m3 HR foam, 10mm layer of 35kg/m3 HR foam.

FEET

Solid wooden feet in beech, oak or walnut

GLIDERS

Solid wooden feet in beech, oak or walnut

SPECIAL FEATURES

Please note that the base frame still needs to be fitted under the seat shell after delivery. This takes about 4 minutes per chair, even for those without prior experience.

UPHOLSTERY

Cover	Fixed (cm)*	Loose fixed (cm)*	Loose cover (cm)*	Leather (m²)*
Uni	110	-	-	1.7
Bi**	(a) -	(a) -	(a) -	(a) -
	(b) -	(b) -	(b) -	(b) -

 * fabric or faux leather metres needs in cm on a roll width of 140cm, leather needs per $^{\rm m^2}$


Leather and faux-leather upholsteries (always fixed)

** The first upholstery (a) is always used for the seat.

SECURITY

This product does not require any specific safety warnings, as it is safe to use under normal conditions.

DIMENSIONS (CM)



WEIGHT & PACKAGING

Product net weight: 6.9 Kgs Number of pieces per carton: 1 pc(s) Carton gross weight: -Carton dimensions: 68x60x50