







SAGA C23

(SAGA PM23 BI -A)

VERSIONS

SAGA C2310 (fixed)

DISTRIBUTION

CONTRACT X'clusive collection

RETAIL X'clusive collection

DESIGN

Pierre Wegnez

LABEL

Mobitec labeled product

STRUCTURE

Solid beech wood, glued joints.

HDF panels stapled and glued.

The armrests are made of steel tube with a diameter of 15mm.

The seat is equipped with Nosag springs.

To allow for the attachment of the central legs, 2 intermediate crosspieces are added to the seat frame.

PADDING

Seat cushion with 4 successive layers: One layer of 20mm polyether foam with a density of 55kg/m^3 , a layer of 20mm HR foam with a density of 43kg/m^3 , a layer of 20mm HT foam with a density of 45kg/m^3 & one layer of 100g/m^2 wadding

Back cushion with 3 successive layers: One layer of 10mm polyether foam with a density of 55kg/m^3 , a layer of 10mm HR foam with a density of 35kg/m^3 & one layer of 20mm HD foam with a density of 55kg/m^3

FEET

360-degree rotating mechanism without automatic return system.

The central legs are fixed to the seat with 4 M6x35 screws.

GLIDERS

SPECIAL FEATURES

UPHOLSTERY

Cover	Fixed (cm)*	Loose fixed (cm)*	Loose cover (cm)*	Leather (m²)*
Uni	-	-	-	-
Bi**	(a) 110	(a) -	(a) -	(a) 1.8
	(b) 75	(b) -	(b) -	(b) 1

^{*} fabric or faux leather metres needs in cm on a roll width of 140cm, leather needs per m

SECURITY

This product does not require any specific safety warnings, as it is safe to use under normal conditions.

DIMENSIONS (CM)



WEIGHT & PACKAGING

Product net weight: 11.8 Kgs Number of pieces per carton: -Carton gross weight: 14.9 Kgs Carton dimensions: 640x620x780



Leather and faux-leather upholsteries (always fixed)

 $[\]ensuremath{^{\star\star}}$ The first upholstery (a) is always used for the seat.